



10/5/04 638



INVESTOR IN PEOPLE

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office
Concept House
Cardiff Road
Newport
South Wales

NP10 8QQ

REC'D 24 FEB 2004

WIPO

PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Andrew Gersey

Dated

17 February 2004

23 2002

LONDON

The
Patent
Office

24OCT02 E758039-4 001631

P01/7700 0.00-0224665 Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

Request for grant of a patent

*See the notes on the back of this form. You can also get
an explanatory leaflet from the Patent Office to help
you fill in this form.)*

Fee: £0

1. Your reference

KEG/45006.GB01

2. Patent application number

(The Patent Office will fill in this part)

0224665.0

23 OCT 2002

3. Full name, address and postcode of the or of
each applicant (*underline all surnames*)Filtrona International Limited
110 Park Street,
LONDON
W1Y.3RB.Patents ADP number (*if you know it*)

7617996001

If the applicant is a corporate body, give the
country/state of incorporation

GB

4. Title of the invention

Smokers Filter

5. Full name, address and postcode in the United
Kingdom to which all correspondence relating
to this form and translation should be sentReddie & Grose
16 Theobalds Road
LONDON
WC1X 8PLPatents ADP number (*if you know it*)

91001 ✓

6. If you are declaring priority from one or more
earlier patent applications, give the country
and the date of filing of the or of each of these
earlier applications and (*if you know it*) the or
each application number

Country

Priority application
(*If you know it*)Date of filing
(*day/month/year*)7. If this application is divided or otherwise
derived from an earlier UK application,
give the number and the filing date of
the earlier application

Number of earlier application

Date of filing
(*day/month/year*)8. Is a statement of inventorship and of right
to grant of a patent required in support of
this request? (*Answer 'Yes' if:*

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an
applicant, or
- c) any named applicant is a corporate body.
See note (d))

YES

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document.

Confirmation sheets of this form

Description 18

Claim(s) 04

Abstract

Drawing(s) 03

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)

01

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

23 October 2002

12. Name and daytime telephone number of person to contact in the United Kingdom

K E GEERING - Reddie & Grose
020-7242 0901

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

BEST AVAILABLE COPY

Patents Form 1/77

SMOKERS FILTER

The present invention relates to tobacco smoke filters, especially for cigarettes.

Some conventional filter cigarettes have a CO/Tar
5 delivery ratio (each measured in mg per cigarette) of a
little less than unity, though this ratio is more usually
unity or greater. Tar is herein defined as Particulate
Matter, Water- and Nicotine-free (PMWNF). It is very
desirable to reduce CO delivery, but prior measures aimed
10 at achieving this have resulted in unsatisfying taste
delivery and/or in unsatisfactory draw performance,
and/or have involved expensive filter structures.

Applicants have now surprisingly found that reduced
CO delivery and reduced CO/tar delivery ratio with
15 maintained smoker satisfaction can be provided by using
a simple and cheaply constructed low tar retention filter
having a relatively high draw resistance low tar
retention downstream filtering plug, a relatively low
draw resistance low tar retention upstream filtering plug
20 spaced longitudinally upstream therefrom, and a filter
wrapper engaged around and joining the spaced filtering
plugs and defining a ventilated cavity therebetween.

The present invention provides a tobacco smoke filter which has a tar retention of at most 50% and comprises a relatively high draw resistance downstream filtering plug of at most 50% tar retention, a relatively low draw resistance upstream filter plug of at most 20% tar retention spaced longitudinally upstream therefrom, and a filter wrapper engaging around and joining the spaced plugs to define a cavity therebetween. The terms "relatively high" and "relatively low" are used to mean that the downstream plug draw resistance is higher than that of the upstream plug. The tar retention of the upstream plug is preferably less than that of the downstream plug. The downstream filtering plug preferably extends to the buccal end face of the filter. The upstream filtering plug preferably extends to the upstream end face of the filter. The cavity may contain particulate additive, e.g. particulate sorbent, preferably activated carbon.

In a filter cigarette according to the invention such a filter is joined to a wrapped tobacco rod with the upstream filter end towards the tobacco, and the cavity is ventilated - i.e. a pathway is provided for external ventilating air to pass laterally into the cavity. The filter may for example be joined to the wrapped tobacco rod by ring tipping (which engages around just the

adjacent ends of filter and rod to leave much of the filter wrapper exposed) or by a full tipping overwrap (which engages around the full filter length and the adjacent end of the rod).

5 The filter wrapper of the filter per se, before incorporation in a filter cigarette, may be a ventilating wrapper (which provides a pathway for the passage of external ventilating air laterally therethrough into the cavity) or it may be non-ventilating. The filter wrapper
10 may have one or more air-permeable regions in register with the cavity, or it may be wholly of air-impermeable or inherently air-permeable material; in each of these cases the filter wrapper may have one or more ventilating holes or apertures (e.g. perforations) around the cavity,
15 but this is optional and in many instances an apertured filter wrapper is not necessary for the unattached filter per se. Where the unattached filter has a filter wrapper of air-impermeable material and is to be used in conjunction with a full tipping overwrap of inherently
20 air-permeable material, then it could be most convenient for the filter wrapper of the unattached filter to have one or more apertures in register with the cavity; this is not the most preferred arrangement, however, and more usually the filter wrappers of the unattached filters
25 will not have ventilating apertures. Thus when the

filter wrapper is of inherently air-permeable material,
ventilating apertures (though not precluded) are usually
unnecessary; and where an apertured filter wrapper is
required, it will frequently be preferred to form the or
5 each ventilating hole in the filter wrapper only during
or after attachment of the preformed filter to a wrapped
tobacco rod in production of the filter cigarette
according to the invention.

In filter cigarettes according to the invention the
10 wall around the cavity (e.g. the filter wrapper when ring
tipping is used, or the combination of filter wrapper and
tipping overwrap) must be ventilating - i.e. provide a
pathway for the passage of external ventilating air
laterally therethrough into the cavity. A tipping
15 overwrap in a filter cigarette according to the invention
must thus be a ventilating overwrap around a ventilating
filter wrapper; the tipping overwrap may for example have
one or more air-permeable regions or be wholly of
inherently air-permeable material, and/or it may have
20 one or more ventilating holes or apertures (e.g.
perforations); and a ventilating pathway thus provided
through the tipping overwrap should of course be in
register with a ventilating pathway through the filter
wrapper and with the cavity.

In one preferred embodiment of filter cigarette according to the invention the filter wrapper is of inherently air-permeable material, and an apertured (e.g. perforated) tipping overwrap, with one or more holes around the cavity, is employed to incorporate the filter in a filter cigarette. Another preferred embodiment uses a tipping overwrap with no ventilating holes to join a wrapped tobacco rod to a filter according to the invention having a filter wrapper with no ventilating holes, and coinciding holes or apertures (e.g. perforations) around the cavity are formed simultaneously through both overwrap and underlying filter wrapper to provide for ventilation into the cavity

Ventilating perforations when present in a filter wrapper and/or tipping overwrap will usually be distributed in one or more rows extending longitudinally of or around the cavity, but other arrangements are possible, and ventilation can be augmented (or provided instead) by larger holes or apertures of any arrangement or distribution.

The filter may be of conventional length - e.g. from 25 to 30 mm. The cavity may for example be from 5 to 10 mm long. The downstream filtering plug may be of about the same length as the upstream filtering plug

specs\45006GB01.2002

(e.g. about 10 mm), but the upstream plug could be the shorter of the two.

The pressure drop (PD) - also termed draw resistance (DR) - of the downstream filtering plug can for example
5 be from 40 to 130 mm water gauge (WG), preferably from 60 to 110 mm WG, e.g. about 90 mm WG. The tar retention of the downstream filter plug is preferably from 30 to 50%, more preferably from 35 to 45%, e.g. about 40%. The pressure drop of the upstream filtering plug can for
10 example be up to 20 mm WG, preferably from 8 to 16 mm WG, e.g. about 12 mm WG. The tar retention of the upstream filtering plug is up to 22%, preferably from 14 to 20%, e.g. about 18%.

The downstream filtering plug is preferably of
15 bonded filamentary tow and its required performance can be obtained by using high denier filaments (for low retention) and high total denier tow (for high pressure drop per unit length). Filamentary cellulose acetate tow is preferred, suitably of a filament denier of at least
20 5 (e.g. 7 or 8 or 9) and a total tow denier of 70 to 80 $\times 10^3$ (e.g. about 75×10^3). An NWA (non-wrapped acetate) filtering plug is preferred - made, for example, as described in GB-A-1,169,932. Other fibrous and non-fibrous downstream filtering plug materials and

structures can however be used (e.g. a plug of staple fibres or cellular plastics material or a plug of plastics - e.g. HDPE - fibres or filaments) provided that they have appropriate low retention and high draw resistance.

The upstream filtering plug may also be of filamentary tow, which may be of high denier filaments. Filamentary cellulose acetate tow is preferred, suitably of a filament denier of at least 5 (e.g. about 9) but with a total tow denier much less than (e.g. about half) that of the downstream plug so as to ensure the required lower pressure drop; the total denier of the upstream plug tow is for example from 35 to 40 x 10³. A preformed WA (wrapped acetate) upstream filter plug is preferred. Other fibrous and non-fibrous upstream filter plug materials and structures can however be used (e.g. a plug of staple fibres or cellular plastics material or a plug of plastics - e.g. HDPE - fibres or filaments) provided that they give appropriate low retention and low draw resistance.

The degree of ventilation can be chosen according to the other details of the structure and the performance required of the final product, but will normally be high - e.g. from 50 to 75% or higher.

Commercially viable filters according to the invention giving satisfactory taste and draw performance in filter cigarettes can provide low CO delivery (usually less than 5 mg per cigarette compared to the value of about 6 mg per cigarette usually delivered by conventional ventilated filter cigarettes) and a low CO/Tar delivery ratio (usually less than 0.7 and preferably as low as 0.6 or less, compared to the usual value of about 1 for conventional ventilated filter cigarettes).

The filters according to the invention may be made by a continuous in-line single pass procedure. In this procedure upstream and downstream plugs are fed alternately at a constant spacing onto a continuously supplied and longitudinally advanced ribbon of filter wrapper material and the ribbon and plugs thereon are continuously passed into and through a garniture which forms the assembly into a continuous rod of spaced plugs within the cylindrical wrapper which is secured by a lapped and stuck seam. The initial continuous rod as it issues continuously from the machine outlet is cut into finite lengths for subsequent use. This cutting may be into individual filters as defined and described above, each of which is then attached to an individual wrapped tobacco rod to form a filter cigarette. More usually,

however, the continuously issuing rod is first cut into double or higher multiple (usually quadruple or sextuple) lengths for subsequent use; when the initial cut is into quadruple or higher lengths, then the latter are subsequently cut into double lengths for the filter cigarette assembly - in which the double length filter rod is assembled and joined (by ring tipping or full tipping overwrap) between a pair of wrapped tobacco rods with the combination then being severed centrally to give two individual filter cigarettes. For this purpose in the present invention the filter plugs in the initial continuously produced rod are double the lengths of the plugs of the eventual individual filters. The continuous rod and the multiple lengths cut from it have individual filters according to the invention integrally joined end-to-end in mirror image relationship, and the double length rod for the mentioned filter cigarette assembly has a double length downstream plug between opposed single length cavities closed at their distal ends by respective single length upstream plugs, the cut to make the individual filter cigarettes being made laterally midway through the central double length plug. The invention includes the described production procedure and the double and higher multiple length filter rods made thereby.

In the accompanying drawings Figs. 1 and 2 respectively are schematic sectional side elevation views, not to scale, of an individual filter and filter cigarette according to the invention; and Fig. 3 is a similar view of a multiple length rod according to the invention showing how it may be cut to form multiple and eventually individual filter lengths of the invention.

The Fig.1 filter has a cylindrical buccal end filtering plug 2 which is of relatively high draw resistance (pressure drop) and low tar retention, a cylindrical upstream filtering plug 3 which is of relatively low draw resistance (pressure drop) and low tar retention, and a filter wrapper 4 engaged around the plugs to form a cavity 6 therebetween.

Purely for the purpose of illustrating an optional feature (the use for the unattached filter per se of an apertured filter wrapper), the filter wrapper 4 of Fig.1 is shown as having a ring of ventilating perforations 8 therethrough around the cavity 6. In most instances, however, the filter wrapper 4 of the unattached filter will be without any ventilating apertures; thus when the filter wrapper 4 is of inherently air-permeable material it usually need not be apertured, and when an apertured filter wrapper is desired or necessary for the filter

cigarette the perforation or other hole formation may best be performed only after assembly of the preformed filter with a wrapped tobacco rod.

Fig.2 shows a filter of the Fig.1 type joined at its upstream end 7 to a tobacco rod 10 in its own wrap 11 by means of a full tipping overwrap 12 which surrounds and engages the full length of the filter and the adjacent end only of the wrapped tobacco rod 10, 11. Tipping overwrap 12 is shown as having a ring of ventilating perforations 14 around cavity 6 in register with ventilating perforations 8 through filter wrapper 4. When filter wrapper 4 is of inherently air-permeable material, perforations 8 may be unnecessary and absent, with perforations 14 being formed in overwrap 12 before assembly of the filter cigarette. When both perforations 8 and 14 are present, they are most conveniently formed simultaneously through filter wrapper 4 and tipping overwrap 12 only after assembly of the filter cigarette, so that perforations 8 and 14 coincide.

The filter of Fig.1 might alternatively be attached to wrapped tobacco rod 10, 11 by ring tipping which extends only around the adjacent ends of the filter and tobacco rod, so that most of filter wrapper 4 is directly exposed to atmosphere. Filter wrapper 4 would then

usually be of air-permeable material, and/or provided with one or more apertures around cavity 6 (before or after filter cigarette assembly), to give ventilation into cavity 6.

5 Fig.3 illustrates multiple length filter rods according to the invention. For Fig.3 a multiple length filter rod is made continuously as described above; this filter rod continuously emerging longitudinally from a production machine outlet (not shown) to the right of
10 Fig.3 has plugs 2' and 3' double the length of above eventual individual filtering plugs 2 and 3, spaced apart in filter wrapper 4 by cavities 6 the same length as those of the eventual individual filters 6. Lines B mark the leading edge of the illustrated sextuple length
15 filter rod, and lines B' the position for its trailing edge and also the location of a cutting device (not shown) downstream of said machine outlet. The advancing filter rod is about to be cut through a double length plug 3' at said location to form said trailing edge 7 and
20 separate the sextuple length, whose leading edge 7 was formed at lines B when this rod position earlier passed said location. The part of Fig.3 to the left of lines B indicates schematically the trailing end of the previously separated sextuple length filter rod, and that
25 to the right of lines B' the leading end of the next to

be formed. When a sextuple length filter rod as illustrated is to be used in filter cigarette manufacture it is first cut simultaneously through double length plugs 3' at lines A and A' to give three identical double
5 length filter rods, each having a central double length plug 2' with a cavity 6 at each end closed by a single length plug 3. As previously described, each double length filter rod is then aligned between and joined to two wrapped tobacco rods and cut midway through the
10 double length plug 2' to give two filter cigarettes of the invention. It will be evident that the continuously formed filter rod could be cut initially into other multiple (e.g. double or quadruple or octuple) lengths; and/or that single length filters as in Fig.1, cut from
15 multiple lengths or directly from the continuously formed filter rod, could be attached individually to single wrapped tobacco rods.

Fig.3 shows the perforations 8 of Fig.1, but as explained in connection with Figs.1 and 2, these
20 perforations are optional and may be absent.

Example

In a specific example of a filter and filter cigarette according to the invention as described with

reference to Figs.1 and 2, the filter is 27 mm long and about 25 mm in circumference. The buccal end plug 2 is a 10 mm long NWA plug - i.e. a preformed non-wrapped plug of plasticised cellulose acetate filaments gathered and bonded together; it is made of a mixture of two tows from two respective bales, one bale being of 8/39 denier - i.e. 8 dpf (denier per filament) and 39×10^3 total denier - and the other being of 7/34 denier to give a 7-8/73 denier product. A given tow specification can be processed differently to yield plugs of different performances; in this Example the processing is such that the 10 mm plug 2 has a PD of 45 mm.WG with a tar retention of under 35%. The upstream end plug 3 is a 10 mm long WA plug - i.e. a preformed wrapped plug of plasticised cellulose acetate filaments - made from a 9/37 denier tow; it has a PD of 10.5 mm.WG with a tar retention of about 16%. The filter wrapper is 27 mm long to give a cavity 7 mm long extending between plugs 2 and 3; it does not have perforations 8 as shown in Figs.1 and 2 and is of air-permeable paper to provide for ventilation into cavity 6. The filter rod is attached by a ventilating tipping overwrap 12 to a commercial wrapped tobacco rod 10, 11. The tipping overwrap paper has a single ring of ventilating perforations 14 around cavity 6 so that on smoking there is ingress of external air laterally through the overwrap perforations and

underlying permeable filter wrapper into the cavity.

The following Table compares the resulting filter cigarette of this Example, which is according to the invention, with a commercial "lights" ventilated filter cigarette using the same tobacco rod with a ventilated WA filter.

	Example	Commercial
Filter Length (mm)	27	27
Filter Construction	NWA + Cavity + WA	WA
Filter Configuration (mm)	10 + 7 + 10	
Tow Selection - NWA Segment	Two bales (8/39 + 7/34)	Not Known
Tow selection - WA Segment	9/37	
Filter PD (mm WG)	66	90
Cigarette Open PD (mm WG)	71	94
Ventilation (%)	52	49
Tar Yield (mg/cig)	8	6.2
Nicotine Yield (mg/cig)	0.66	0.53
CO Yield (mg/cig)	4.9	6.1
CO/Tar Ratio	0.61	0.99

WA indicates "wrapped acetate" - a plug preformed by

gathering cellulose acetate filamentary tow into a plug
constrained in a wrap.

Values for product and component parameters
(including pressure drop, tar retention, % ventilation,
5 permeability) disclosed herein are all as measured using
industry standard (CORESTA) equipment and conditions.
Thus pressure drop (draw resistance) is the pressure
difference between the two ends of the filter or
component concerned at a steady volumetric flow of 17.5
10 ml/sec, and unless indicated as "open" (measured with
ventilation permitted) is measured "enclosed"
(encapsulated in the measuring device, with no
ventilation). Smoke component (tar, CO, nicotine etc)
delivery yields are measured by smoking the cigarette on
15 a standard (Filtrona) smoking machine under standard ISO
conditions (puffs, each of 35 ml volume and 2 seconds
duration, at one minute intervals), and collecting and
analysing the smoke delivered. Filter and filter plug
retention efficiencies are calculated by smoking the
20 cigarette with the filter enclosed (no ventilation) and
measuring the weight of tar retention by the plug(s)
concerned; the tar retention is the ratio, expressed as
a percentage, of this weight of tar retained in the used
plug(s) to the total weight of said retained tar and
25 delivered tar yield. The percentage ventilation (or air

dilution) is the proportion of ventilating air present in the total volumetric flow from the buccal end of the cigarette; it is measured on the unlit cigarette with said total flow set at 17.5 ml/second; in practice 50%
5 ventilation or air dilution indicates that on smoking each puff will contain an about 50/50 v/v ratio of added ventilating air to original smoke, and 40% ventilation indicates an about 40/60 ratio and so on. The CORESTA (Centre de Cooperation pour les Recherches Scientifique
10 Relatives au Tabac) unit of air permeability is ml/min.cm² under 1 kPa.

The ISO tests used for parameter measurements herein include :

Tar Yield - ISO 4387 (Cigarettes - Determination of Total
15 and Nicotine-free Dry Particulate Matter using a Routine Analytical Smoking Machine).

Carbon Monoxide Yield - ISO 8454 (Cigarettes - Determination of Carbon Monoxide in the Vapour Phase of Cigarette Smoke - NDIR Method).

20 Paper Permeability - ISO 2965 (Materials used as Cigarette Papers, Filter Plug Wrap and Filter Joining Pap, including Materials having an Oriented Permeable Zone - Determination

- 18 -

of Air Permeability).

C L A I M S :

1. A tobacco smoke filter which has a tar retention of at most 50% and comprises a relatively high draw resistance downstream filtering plug of at most 50% tar retention, a relatively low draw resistance upstream filter plug of at most 22% tar retention spaced longitudinally upstream therefrom, and a filter wrapper engaging around and joining the spaced plugs to define a cavity therebetween.
2. A filter according to claim 1 wherein the downstream filtering plug has a draw resistance of from 40 to 130 mm.WG.
3. A filter according to claim 2 wherein the downstream filtering plug has a draw resistance of from 60 to 110 mm.WG.
4. A filter according to any preceding claim wherein the downstream filtering plug has a tar retention of from 35 to 45%.
5. A filter according to any preceding claim wherein

the upstream filtering plug has a draw resistance of up to 20 mm.WG.

6. A filter according to any preceding claim wherein the upstream filtering plug has a draw resistance of to
5 8 to 16 mm.WG.

7. A filter according to any preceding claim wherein the upstream filtering plug has a tar retention of from 14 to 20%.

8. A filter according to any preceding claim wherein
10 the filter wrapper is a ventilating wrapper.

9. A filter according to claim 8 wherein the filter wrapper is of air-permeable material and/or has one or more ventilating apertures in register with the cavity.

10. A filter cigarette comprising a filter according to
15 any preceding claim joined at its upstream end to a wrapped tobacco rod, a pathway being provided for the passage of external ventilating air laterally into the cavity.

11. A filter cigarette according to claim 10 wherein

filter and wrapped tobacco rod are joined by ring tipping.

12. A filter cigarette according to claim 10 wherein filter and wrapped tobacco rod are joined by a full
5 tipping overwrap, the filter wrapper and overwrap together providing a pathway for external ventilating air to pass laterally therethrough into the cavity.

13. A filter cigarette according to claim 12 wherein the filter wrapper is of air-permeable material and the
10 tipping overwrap has one or more ventilating apertures in register with the cavity.

14. A filter cigarette according to claim 12 wherein the tipping overwrap has one or more ventilating apertures in register with one or more ventilating apertures in the
15 filter wrapper and with the cavity.

15. A filter cigarette according to any of claims 10 to 14 having a CO delivery of less than 5 mg. and a CO/tar delivery ratio of less than 0.7.

16. A multiple length filter rod comprising a plurality
20 of filters according to any of claims 1 to 9 joined

integrally end-to-end in mirror image relationship.

17. A tobacco smoke filter substantially as hereinbefore described with reference to the accompanying drawings.

18. A filter cigarette substantially as hereinbefore
5 described with reference to the accompanying drawings.

19. A method of making a tobacco smoke filter, the method being substantially as hereinbefore described.

20. A method of making a filter cigarette, the method being substantially as hereinbefore described.

10 21. A filter according to claim 1 and substantially as hereinbefore described in the Example.

22. A filter cigarette according to claim 10 and substantially as hereinbefore described in the Example.




FIGURE 1




FIGURE 2

FIGURE 3

